



Figure similar

SIMATIC S7-200 SMART, Analog input SM AI04, 4 AI, 0...10V, 0...5V, +/-5 V, +/-2.5 V, or 0/4-20 mA 11 bit + sign (12 bit ADC)

General information	
Product type designation	SM AI04, AI 4x12 bit
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; -15 / +20 %
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	40 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4
Input ranges	
<ul style="list-style-type: none"> • Voltage 	Yes; ±10V, ±5V, ±2.5V
<ul style="list-style-type: none"> • Current 	Yes; 0 to 20 mA
<ul style="list-style-type: none"> • Thermocouple 	No
<ul style="list-style-type: none"> • Resistance thermometer 	No
<ul style="list-style-type: none"> • Resistance 	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • -10 V to +10 V — Input resistance (-10 V to +10 V) 	Yes 9 MΩ
<ul style="list-style-type: none"> • -2.5 V to +2.5 V — Input resistance (-2.5 V to +2.5 V) 	Yes 9 MΩ
<ul style="list-style-type: none"> • -5 V to +5 V — Input resistance (-5 V to +5 V) 	Yes 9 MΩ
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA — Input resistance (0 to 20 mA) 	Yes 250 Ω
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Interference voltage suppression for interference frequency f1 in Hz 	12 bit; voltage mode: 11 bit + sign bit, current mode: 11 bit 10 / 50 / 60 / 400 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> • parameterizable 	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time

- Step: None
- Step: low
- Step: Medium
- Step: High

Yes; 1x
 Yes; 4x
 Yes; 16x
 Yes; 32x

Interrupts/diagnostics/status information

Diagnostics function	Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage • Wire-break • Short-circuit 	<p>Yes No No</p>
Diagnostics indication LED	
<ul style="list-style-type: none"> • for status of the inputs 	Yes

Degree and class of protection

IP degree of protection	IP20
-------------------------	------

Standards, approvals, certificates

CE mark	Yes
---------	-----

Dimensions

Width	45 mm
Height	100 mm
Depth	81 mm

Weights

Weight, approx.	147 g
-----------------	-------

last modified: 3/12/2024 