6GK5005-0BA00-1AB2

Data sheet



SCALANCE XB005 unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 5x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download .

product type designation	
product brand name	SCALANCE
product type designation	XB005
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	5; RJ45
number of 100 Mbit/s SC ports	
• for multimode	0
interfaces / other	
number of electrical connections	
for power supply	1
type of electrical connection	
for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
 supply voltage / 1 / rated value 	24 V
power loss [W] / 1 / rated value	1.68 W
 supply voltage / 1 / rated value 	19.2 28.8 V
consumed current / 1 / maximum	0.07 A
 type of electrical connection / 1 / for power supply 	3-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V
type of voltage / 2 / of the supply voltage	AC
supply voltage / 2 / rated value	19.2 28.8 V
ambient conditions	
ambient temperature	
 during operation 	-10 +60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Box
width	45 mm
height	100 mm
depth	87 mm

net weight	0.165 kg	
fastening method		
 35 mm top hat DIN rail mounting 	Yes	
wall mounting	Yes	
S7-1500 rail mounting	No	
product functions / management, configuration, engineering		
product function		
 multiport mirroring 	No	
• CoS	Yes	
PROFINET conformity class	A	
product function / switch-managed	No	
product functions / redundancy		
product function		
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes	
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No	
standards, specifications, approvals		
certificate of suitability / CE marking	Yes	
standard / for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1	
certificate of suitability	02 00000 1, 007 (022.2 110. 00000 1	
KC approval	Yes	
Regulatory Compliance Mark (RCM)	Yes	
standards, specifications, approvals / hazardous environments	160	
certificate of suitability	V	
• ATEX	Yes	
• UKEX	Yes	
• IECEX	Yes	
ULhazloc approval	Yes	
 CCC / for hazardous zone according to GB standard 	Yes	
FM registration	Yes	
standards, specifications, approvals / Environmental Product De	eclaration	
Environmental Product Declaration	Yes	
Global Warming Potential [CO2 eq]		
● total	151.5 kg	
 during manufacturing 	7.42 kg	
 during operation 	143.95 kg	
after end of life	0.14 kg	
product functions / general		
MTBF	241 a	
reference code		
• according to IEC 81346-2	KF	
 according to IEC 81346-2:2019 	KFE	
Warranty period	5 a	
further information / internet links		
internet link		
to website: Image database	https://www.automation.siemens.com/bilddb	
to website: Image database to website: Industry Online Support	https://support.industry.siemens.com	
security information	The state of the s	
security information	Siemens provides products and solutions with industrial cybersecurity functions	
	that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase	

customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration



Declaration of Conformity







EMV For use in hazardous locations **Test Certificates**

<u>KC</u>



<u>FM</u>

CCC-Ex

Special Test Certific-<u>ate</u>

Environment

Industrial Communication

Confirmation



PROFINET

last modified:

4/9/2024

